

## SPIRO® PLASMACUTTERS

**Spiro® has been renowned for advanced plasma cutting systems since 1992.**

The sound reputation stems from continuous development and redesign efforts to maintain the leading edge technology, including the self-developed Spiro® Control System, high-quality mechanical components

combined with Hypertherm as the leading powermax unit, as well as the compatibility with the HVAC Cam-Duct software.

TECHNICAL DATA		
PLASMACUTTER	FLORETT	CUTLASS
Work Area	1500 x 3000 mm (5' x 10')	1500 x 6000 mm (5' x 20')
Output	300 segments/hour – size 315 mm/90°	240 segments/hour – size 315 mm/90°
Traverse Speed	40 m/min. (131 fpm) both X- and Y-axis	>22 m/min (>72 fpm)
Power Supply	4 kVA / 380 – 480 V / 50 or 60 Hz / 3-phases	4 kVA / 380 – 480 V / 50 or 60 Hz / 3-phases

## PLASMACUTTER FLORETT

### Unique Features:

- Spiro® HS Controller v.3
- 50% faster traverse speed
- Total production time reduced up to 20%
- Enforced high precision linear unit for the torch
- Belt driven technology



## PLASMACUTTER CUTLASS

### Unique Features:

- Spiro® HS Controller v.3
- Enforced high precision linear unit for the torch
- Step forward/backward function
- Free mode, select any part or contour
- Optimized sheet utilization
- Remote Internet access for technical support